



# KRAMER

## VS-88HDxI

8x8 3G HD-SDI Matrix Switcher

| 3G HD-SDI - BNC | Ethernet - RJ-45



The VS-88HDxI is a high-performance matrix switcher for 3G HD-SDI and HD-SDI dual link video signals. The unit can switch any or all inputs to any or all outputs. Switching is implemented during the vertical interval period according to the SMPTE RP-168 standard, when using synchronized digital video sources

### FEATURES

**Max. Data Rate** - 3Gbps

**Multi-Standard Operation** - SDI (SMPTE 259M & SMPTE 344M), HD-SDI (SMPTE 292M), 3G HD-SDI (SMPTE 424M) and dual link HD-SDI (SMPTE 372M)

**Automatic Equalization Technology**

**Looping Analog Sync Input**

**Selectable Sync Signal Termination**

**Analog Sync Type** - Bi-level, tri-level

**Take Button** - Executes multiple switches all at once

**Multiple Memory Locations** - Stores multiple switches as presets (salvos) to be recalled and executed when needed

**Vertical Interval Switching** - Synchronizes either to external reference or the incoming video in compliance with SMPTE RP-168

**Flexible Control Options** - Front panel, RS-232 (K-Router Plus™ Windows®-based software is included), RS-485, Ethernet, contact closure & IR remote (available upon request)

**Front Panel Control Lockout**

**Worldwide Power Supply** - 100-240V AC

**Standard 19" Rack Mount Size** - 1U. Rack "ears" included



# KRAMER

## TECHNICAL SPECIFICATIONS

INPUTS:	8 SMPTE-259M, 344M, 292M, 372M, 424M serial video, 75Ω on BNC connectors
OUTPUTS:	8 equalized and reclocked SMPTE-259M, 344M, 292M, 424M, 372M (dual link) outputs 75Ω on BNC connectors
MAX. OUTPUT LEVEL:	800mVpp/75Ω
DATA RATE:	Up to 2.97Gbps
CONTROLS:	Front-panel, RS-232, RS-485, ETHERNET, remote infrared
INDICATORS:	8-character display on the front panel
POWER CONSUMPTION:	Universal, 100-240V AC, 50/60Hz 24VA
INCLUDED ACCESSORIES:	Power cord, IR remote control transmitter (upon request)
OPTIONS:	External remote IR receiver cable
Product Dimensions	19" x 9.34 x 1U (43.6cm x 23.72cm x 4.36cm) W, D, H
Product Weight	1.9kg (4.2lbs) approx
Shipping Dimensions	52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21" ) W, D, H
Shipping Weight	2.9kg (6.4lbs) approx

