

WM 43/48/56 C1R

WM 70 C2R Pluggable/Fixed Gooseneck Microphones



Features

- Uni-directional microphone stem
- Pluggable/fixed gooseneck microphone

The stylish and elegant designed microphone with an adjustable stem simply plugs directly into a table-top & flush-mounted conference discussion unit.

It is equipped with a uni-directional response for optimum performance even in noisy circumstances, and has low susceptibility to interference from cell phones.

Functions

Controls and Indicators

- Red Ring of Light illuminator indicates microphone is active and request-to-speak status (red illuminator is keep flashing)

Interconnections

- Connector to plug and fasten the microphone with quick screw ring

TECHNICAL SPECIFICATIONS

Cartridge Type	Electret
Directivity	Unidirectional
Frequency Response	80-16000Hz
Polar Pattern	Cardioid
Output Impedance	≤680Ω
Sensitivity	-47±3dB(0dB=1V/Pa,at 1KHz)
Maximum SPL	110dB(THD <1%, at 1KHz)
S/N Ratio	60dB
Operating voltage	5-8V
MODEL/LENGTH/WEIGHT	WM-43C1R/ 430 mm/ 100 g (0.22 lb)
	WM-48C1R/ 480 mm/ 107 g (0.24 lb)
	WM-56C1R /560 mm/ 117 g (0.26 lb)
	WM-70C2R/ 700 mm/ 137 g (0.30 lb)

*The appearance and specifications of all item are subject to change without notice