



## Yarden 6-O

6.5-Inch, 2-Way On-Wall Speakers

| Speakers



The Yarden 6-O High Performance On-wall Speaker features a Kevlar(R) woofer, 2nd level cross-over design and multi-tap power transformer for selecting 8 $\Omega$  (bypassing the transformer) or 70V/100V power settings that are suitable for an array installation

### FEATURES

Type - 2-way on-wall speaker

Woofer - 6.5" Kevlar(R) cone

Tweeter - 1" titanium dome

Impedance - 8 $\Omega$

Power Handling - 80W RMS, 220W continuous program

Transformer Taps - 70V: 60W /30W/15W/7.5W/Off (Lo-Z); 100V: 60W/30W /15W/Off (Lo-Z)

Package - 2 speakers (1 pair)




# KRAMER

## TECHNICAL SPECIFICATIONS

---

|                                    |  |
|------------------------------------|--|
| DESCRIPTION:                       | 2-way on-wall speakers   |
| FREQUENCY RESPONSE:                | 65Hz to 20kHz @-10dB, 83Hz to 20kHz @±3dB  |
| WOOFER:                            | 6.5" (166mm) Kevlar(R) with rubber surround  |
| TWEETER:                           | 1" (25.4mm) titanium   |
| IMPEDANCE:                         | 8Ω (transformer tap in off position)   |
| TRANSFORMER TAPS:                  | 70V – 60W/30W/15W/7.5W/Off (Lo-Z), 100V – 60W/30W/15W/Off (Lo-Z)   |
| SENSITIVITY:                       | 86dB SPL, 1W@1m  |
| MAX SPL:                           | Continuous: 104dB, peak: 107dB   |
| POWER HANDLING:                    | 80W RMS, 220W continuous program   |
| CROSSOVER FREQUENCY:               | 1.9kHz   |
| DIRECTIVITY FACTOR (Q):            | 7.1 averaged 1kHz to 10kHz   |
| DIRECTIVITY INDEX (DI):            | 8.5dB averaged 1kHz to 10kHz   |
| INPUT CONNECTORS:                  | Terminal blocks  |
| MATERIALS:                         | Frame, aluminum grill, steel brackets and ABS cabinet  |
| OPERATING TEMPERATURE:             | 0° to +40°C (32° to 104°F)   |
| STORAGE TEMPERATURE:               | -40° to +70°C (-40° to 158°F)  |
| HUMIDITY:                          | 10% to 90%, RHL non-condensing   |
| WEIGHT PER SINGLE SPEAKER:         | 3.93kg (8.66lb) approx   |
| WEIGHT WITH MOUNTING KIT:          | 4.18kg (9.22lb) approx   |
| SHIPPING WEIGHT (FOR PAIR):        | 9kg (19.84lb) approx   |
| DIMENSIONS WITH MOUNTING BRACKETS: | 21.5cm x 22.5cm x 30.1cm (8.5" x 8.9" x 11.9"), W, D, H  |
| INSTALLATION CLEARANCE:            | Front panel to wall (with mounting bracket): 22.7cm (8.9"); back panel to wall (with mounting bracket): 3.8cm (1.5") |
| ACCESSORIES:                       | 2 mounting brackets (including 4 knobs and 4 mounting screws)  |
| OPTIONS:                           | BCP-2S speaker cable   |
| COLORS:                            | Available in white   |



Color Key: ● HDMI ● Audio ● VGA ● ETH