

# ZH 701-S5

## High Speed Camera



- High speed tilt and **360°** endless rotation and auto flip function allows this speed dome to be installed in the most demanding applications.
  - **RS-485 & RS-232** communication channel is available for remote control purposes.
  - **128** preset points can be programmed for precise location of target areas, you can also define multiple cruise routes for the camera to operate automatically.
  - Compact lightweight design for easy installation
  - Weatherproof housing
  - High resolution **480** TV lines
  - All-in-one type
  - Precise and Accurate Dome Camera
- Performance
- Preset speed up to 400°/sec.
  - Preset accuracy of 0.225°
  - Proportional Pan & Tilt Speed
  - Preset Position / Auto-Pan / Sequence / Cruise
  - Auto-Calibration

### TECHNICAL SPECIFICATIONS

CCD Sensor	1/4" CCD	
Optical Zoom Ratio	30×	
Digital Zoom	1× ~ 12× variable	
Effective Pixels	NTSC	380K
	PAL	440K
Horizontal Resolution	NTSC	480 TVL
	PAL	480 TVL
Scanning System	NTSC / PAL	
Synchronization	Internal / Line Lock	
Video Output	1.0 Vpp / 75 ohm, BNC	
S/N Ratio	> 50 dB (AGC Off)	
Minimum Illumination	1 lux	
Focus Length	4 ~ 88 mm	
Focus Mode	Auto / Manual	
White Balance	Auto / Manual	
Iris Control	Auto / Manual	
Electronic Shutter	NTSC	1/60 ~ 1/30k sec.
	PAL	1/50 ~ 1/30k sec
AGC Control	Auto / Manual	
Back Light Compensation	On / Off	
Dimensions	131 x 226mm	
Weight	1.6kg	
Power	12V, 20W	