

CORIOconsole

Model CC-300



CC-300 CORIOconsole provides a Video Production Switcher type interface for the C2 series Universal Video Processors. Two rows of 14 buttons are provided for Preview and Program functionality of mixed format sources. These buttons are programmable (via the C2 unit attached), to accommodate more than 11 inputs. Fades and wipes are either automatic with preset times or manually controlled via the fader bar. The joystick employs full range of motion to allow precise positioning of PIP inserts and other functions. The Integrated LCD touch screen, plus fixed purpose function keys combine with "soft" function keys to provide total control over multiple C2 series units. The CC-300 provides access to all controls with a minimum of keystrokes. The unit is in a low profile desk top case that may also be rack mounted. Control of external devices is available via the unit's direct interface to machine control products made by Calypso Control Systems.



Key Features of the CC-300 CORIOconsole

- Full Control of C2 Series Functions
- Precision Fader and Joystick
- Integrated LCD Touch Screen Display
- **Dedicated Program and Preview Buttons**
- IP and RS-232 Interface
- Low Profile Enclosure Rackmountable

Specifications

Input Selection/Manipulation

Program/Preview Buttons 2x14 inputs; Pgm, Prev, Take Manual Fade/Wipe Via Precision Fader Manual Image Positioning Via Precision Joystick

Mode/Function Selection Dedicated Function Keys 21 (Mode & Cross Functional) "Soft" Function Keys 14 (Variable Functions) Shift Keys 2 (Function Multiplier) Integrated Display Touch Screen LCD 6.5"x3.1"

Environmental

Operating Temperature 0° to +50° C (+32° to +122° F) **Operating Humidity** 10% to 85%, Non-condensing Storage Temperature -10° to +60° C(+14° to +140° F) Storage Humidity 10% to 85%, Non-condensing

Mechanical

Desktop Case 67x432x176mm (2.6"x17"x6.9") (HWD)

Weight (Net)

Warranty

Limited Warranty

Power Requirement

External Power Supply Regulatory Approvals

Converter Unit

Power Supply

Accessories Included

1x Power Adapter

1x Operations Manual

Product Item Number

3.06 kg (6.73 lbs)

2 Years Parts and Labor

12VDC@2A - Locking DC

FCC, CE, RoHS

UL, CUL, CE, PSE, GS, RoHS

US, UK or Euro

CC-300

Panel Drawings

