

CLS225-CCA

Loudspeaker cable - 2 x 2.5 mm² - 13 AWG - EN50399 CPR
Euroclass Cca-s1b,d0,a1

Highlights:

- EN50399 CPR Euroclass Cca-s1b,d0,a1
- 13 AWG (2.5 mm²) thin and dense stranded conductors
- Class 5 IEC 60228 compliant

The CLS225-Cca series are 2-core installation loudspeaker cables compliant to the Cca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its outstanding fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.

More information about CPR compliant cables? [Click here](#)



Certification:



Properties:



Inner Conductors:



Usage:




Physical Characteristics:

EN50399 CPR Euroclass			Cca-s1b,d0,a1
Inner conductor	Insulation	Material	Polyolefin 3.0 mm (Ø)
		Colours	Red / Blue
Outer jacket	Material		Polyolefin 8.5 mm (Ø)
	Colours		Black
Type of cable			2-core loudspeaker cable
Inner conductor	Material		BC 40 x 0.263 mm (Ø) (OFC)
	Section		2.5 mm²
Filling			None
Separator			None
Inner conductor	American Wire Gauge		13 AWG
	Number of conductors		2
Conductor twisting			Yes

Electrical Characteristics:

Max. conductor	DC resistance	7.98 (Ω / Km)
Dielectric strength		2 (KV / 1 min. DC)
Rated voltage		500 V

Cross sections:



Variants:

- CLS225-CCA/1 - 100 m wooden reel
- CLS225-CCA/3 - 300 m wooden reel