

CLS240-B2CA

Loudspeaker cable - 2 x 4 mm² - 11 AWG - EN50399 CPR
Euroclass B2ca-s1b,d0,a1

Highlights:

- 11 AWG (4 mm²) thin and dense stranded conductors
- EN50399 CPR Euroclass B2ca-s1b,d0,a1
- Class 5 IEC 60228 compliant

The CLS240-B2ca series are 2-core installation loudspeaker cables compliant to the B2ca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its outstanding fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.


More information about CPR compliant cables? [Click here](#)



Certification:



Properties:



Inner Conductors:



Usage:




Physical Characteristics:

EN50399 CPR Euroclass		B2ca-s1b,d0,a1	
Inner conductor	Insulation	Material	Polyolefin 4.5 mm (Ø)
		Colours	Red / Blue
Outer jacket	Material	Polyolefin 11.7 mm (Ø)	
	Colours	Black	
Type of cable		2-core loudspeaker cable	
Inner conductor	Material	BC 48 x 0.31 mm (Ø) (OFC)	
	Section	4 mm²	
Filling		None	
Separator		None	
Inner conductor	American Wire Gauge	11 AWG	
	Number of conductors	2	
Conductor twisting		Yes	

Electrical Characteristics:

Max. conductor	DC resistance	4.95 (Ω / Km)
Dielectric strength		2 (KV / 1 min. DC)
Rated voltage		500 V

Cross sections:



Variants:

- CLS240-B2CA/1 - 100 m plastic reel
- CLS240-B2CA/3 - 300 m plastic reel