

eMCONTROL1

ANALOGUE CONTROLS & PANELS

Wall Panel Micro-Mixer



PRODUCT OVERVIEW

eMCONTROL1 is a digital wall control, compatible with eMIMO1616, configurable through the web application embedded in the HUB digital zoner. It allows you to configure source selection, volume control and equalization for a given zone, including all or some of the functions.

It can be combined with a WPa series wall panel, connecting both with a single CAT5 cable or better to the HUB unit, transmitting the mono and balanced audio signal (line level) along with the necessary control data and DC power supply.

KEY FEATURES

- Digital control panel compatible with HUB Series
- Volume adjustment, source selection and EQ (programmable)
- Compatible with WPa series panels with audio connector, for sending audio and control signals over a single CAT5 cable or better
- Styling designed in collaboration with Italdesign Giugiaro

APPLICATIONS


• Remote control of an HUB digital zoner

ACCESSORIES AND COMPATIBLE PRODUCTS

- HUB1408
- HUB1616
- WPaMIX-T
- WPa2FMBOX
- WPa2SMBOX



MECHANICAL DIAGRAMS



TECHNICAL DATA

Digital characteristics	
Control keys	Encoder, SELECTION key
Indicators	LCD display – 128x128 Pixels
Communication standard	RS485
Supply characteristics	
Nominal power supply	From RJ45 remote input: 12VDC
	From External Input: 24VDC
Minimum external power supply	From RJ45 remote input without WPaMIX-T: 9,5V
	From RJ45 remote input with WPaMIX-T: 11V
	From External Input: 18VDC
Maximum power consumption	From RJ45 remote input without WPaMIX-T: 60mA
	From RJ45 remote input with WPaMIX-T: 80mA
	From External Input: 25mA @ 24VDC
Miscellaneous	
Connector	RJ45 remote port
Dimensions (WxHxD)	86x86x45mm
Weight	150g.
Included accessories	Cable to interconnect with WPaMIX-T