

The Kramer Mounting Frame

The Kramer **FLA-12** and/or **FLA-13** mounting frames are used to install Kramer inserts to Ackermann Flush floor service units.

The Kramer **FLA-12** can include up to 4 single Kramer inserts and fits into the GB2 slot of the Ackermann Flush floor service units.



Figure 1: FLA-12

The Kramer **FLA-13** can include up to 5 single Kramer inserts and fits into the GB3 slot of the Ackermann Flush floor service units.



Figure 2: FLA-13

To install a Kramer insert, do the following:

1. Place and align the required wall plate insert item over the opening.
2. Insert the two screws to fix the insert in place, and tighten them.

To install the **FLA-12/FLA-13** inside the Ackermann Floor Box, do the following:

1. Run the cables through the Ackermann underfloor cable opening.
2. Connect the cables to the rear side of the inserts.
3. Fit the **FLA12/FLA13** tab into its designated place in the Ackermann underfloor box.
4. Place the tab with the slot into place in the Ackermann box and tighten the screws in place.
5. Connect the desired cables to the inserts.



Mounting Frame for Ackermann Flush Floor Service Units FLA-12, FLA-13 Installation Instructions

For the latest information on our products and a list of Kramer distributors, visit our
Web site: www.kramerelectronics.com



Kramer Electronics, Ltd.

Web site: www.kramerelectronics.com

E-mail: info@kramerelect.com

P/N: 2900-000571 REV 1