

LED Monitor Light



Smooth gloss black powder coated finish is standard. Custom colors are available by request.

The i-Series, a sleek, energy-efficient LED fixture, is scalable to virtually any monitor. Cool-to-the-touch, the i-Series fixtures make it easy to look your best on camera, allowing individuals to conference remotely without sacrificing critical visual details.

The many non-verbal nuances of facial expression and eye contact are critical to effective communications. The i-Series enhances visual clarity, thereby increasing the readable content within a video image and raising the engagement level of participants in the conference.





Specifications

Construction

.078" thick aluminum extruded housing. Aluminum cast end caps. .09" aluminum reflector powder coated gloss white. A smooth gloss black powder coated finish is standard, with custom colors available by request.

Electrical

6-ft (1.8-m) power cord with built-in low voltage transformer connects to fixture housing using single pin connector. Plug is a NEMA 5-15P and is standard for 120V fixtures. In-line rotary dimming transformer is standard. 12V high-power LED strips mounted on reflector.

Individual Fixture Wattage

i-S/16: 15W i-S/22: 20W i-S/36: 35W i-S/48: 45W i-S/48/D: 90W

Mounting

Mounting brackets sold separately; please specify one of the following on order: VESA 75-100, VESA 100-200, Weighted Base or Mini Clamp. See reverse side for fixture and mounting option compatibility.

Louver and Lens

Fixtures are provided with 1/2" x 1/2" black egg crate louver and LED film.

Dimensions

The fixture has dimensions of 1.71" [43.43m] single or 3.21" [81.53mm] double-high x 3.5" [88.9mm] deep x 16.16" [410.43mm], 22.41" [569.21mm], 36.16" [918.46mm] or 48.03" [1219.96mm] long.





i-Series

LED Monitor Light

The i-Series has many choices of mounting options; please select one per fixture from the guide below.

