MAX® Wireless

Tabletop Conference Phone

The industry's first wireless tabletop conference phone. MAX Wireless provides the flexibility to hold a conference call when and where it's most convenient – with no cables in the way. MAX Wireless is a perfect fit for offices and small conference rooms, and delivers outstanding audio clarity.

ClearOne



UNRIVALED
WIRELESS
AUDIO QUALITY,
FLEXIBILITY AND
AFFORDABILITY

APPLICATIONS

Executive Office

Small Office/Home Office

Small Conference Room

Any room without a phone line

ADVANTAGES

Superior Audio Performance

- + High-quality full duplex sound enables participants to speak and listen at the same time without sound cutting in and out
- + Distributed Echo Cancellation® effectively eliminates echo
- Noise cancellation removes background noises from fans, HVAC systems, lights, projectors, etc.
- + Automatic level controls keep participants' audio balanced and consistent
- + First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Three microphones provide 360° audio pickup

Wireless Capabilities

- + Turn any room into a conference room, even one without a phone line
- + Wireless signal range allows use in multiple rooms without moving the base unit
- + Wireless design provides a clean look with no wires on the table or floor
- + 12 hours of talk time allows for lengthy conferences without recharging; 36 hours of standby time reduces recharging frequency; automatic power-save mode conserves battery life
- + Dual-function power supply/charger enables conferencing while charging
- + DECT Standard cipher with 64-bit encryption ensures secure conferencing
- + Audible warnings sound when phone is out of range
- + Phone paging button allows easy identification of phone's location

Ease of Use & Control

- + Simple plug-and-play functionality makes installation and configuration a snap
- + Field upgradeable for easy access to latest features
- + Selectable ring tones



SPECIFICATIONS

Echo Cancellation

Tail time: 60 ms x 3

Noise Cancellation

Dynamic noise cancellation

Telephone Connection

Analog PBX or PSTN line RJ-11C, -12 dBm nominal

Radio

Standard DECT/DECT 6.0 ETSI EN 300 175 1-9

Keypad

Alphanumeric standard keypad

Loudspeaker

Volume: 90 dBspl A weighted @ 1 ft Bandwidth: 200 Hz-3.3 kHz

Certifications

FCC part 15/ICES-003 Class A FCC part 15 Subpart C/RSS-210 FCC part 68/IC CS-03

UL Certified

Power

Phone unit: Custom battery pack with nickel metal hydride batteries, 7.2 V 2200 mAh 12 hours continuous talk time (typical) 36 hours standby Base unit: Auto-adjusting power module; 100-240 VAC; 50/60Hz

Wireless Range

150 ft (45 m) Note: Range depends on environmental factors and may vary.

Environmental

Operating temperature: 32-118° F (0-48° C) Storage temperature: 41-158° F (5-70° C) Operating humidity: 15 to 80% Storage humidity: 10 to 90%

Dimensions (W x D x H)

Phone unit: 10.5" x 10.5" x 3" (26.7 cm x 26.7 cm x 7.6 cm) Base unit: 4.25" x 5.5" x 2.5' (10.8 cm x 14 cm x 6.4 cm)

Weight

Phone unit: 2.7 lb (1.2 kg) Base unit: .6 lb (0.27 kg) Shipping: MAX Wireless 10 lb (4.5 kg)

MAX Wireless Includes

Wireless phone unit (1) Base unit (1) Battery pack (1) Power supply/charger (1) Power supply retainer (1) Telephone cable Documentation CD Quick start guide

Part Numbers

910-158-600 (North America) 910-158-601 (Europe/UK) 910-158-602 (Australia/New Zealand) 910-158-603 (Hong Kong/Singapore)

ROOM APPLICATIONS

MAX Wireless is a single conference phone that connects wirelessly to a base unit for use in any small room.





CLEARONE LOCATIONS

Salt Lake City, UT USA 5225 Wiley Post Way Suite 500 Salt Lake City, UT 84116 Tel: 801-975-7200 Toll Free: 800-945-7730 Fax: 801-303-5711 sales@clearone.com

Latin America Tel: 801-974-3621 global@clearone.com

Tel: 44 (0) 1189 036 053

Tel: 801-303-3388 global@clearone.com Asia-Pacific Support Center Tel: 852-3590-4526 techsupport.apac@clearone.com