

NAC3MPX-TOP

Appliance inlet connector, 1/4" flat tab terminals

The powerCON TRUE1 TOP is a locking 16 A true mains connector for outdoor applications. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

The powerCON TRUE1 TOP is a connector with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live.



Features & Benefits

- Heavy duty sealed power connector for harsh and demanding environment
- Uses high impact UV-resistant materials
- Lockable 16 A single phase connector (USA: 20 A)
- Extremely robust and reliable
- ENEC certified according to IEC 60320
- IP65, UL50E enclosure type4 rating in combination with SCNAC-MPX(mated or with closed cap)
- True mains connector with breaking capacity (CBC)
- Easy and reliable twist lock system
- Unique Neutrik cable retention
- UL498 certified

Technical Information

| Product | |
|--------------|-------------|
| Title | NAC3MPX-TOP |

| Electrical | |
|--------------------------------------|-------------------------------|
| Contact resistance | ≤ 2 mΩ |
| Dielectric strength | 4 kVdc / 2.8 kVac |
| Insulation resistance | > 1 GΩ (after damp heat test) |
| Number of electrical contacts | 2 + PE |
| Rated current per contact | 16 A rms (USA: 20 A) |
| Rated voltage | 250 V ac |

| Mechanical | |
|-----------------|----------------------|
| Lifetime | > 5000 mating cycles |
| Wiresize | 2.5 mm ² |
| Wiresize | 12 AWG |

| Material | |
|------------------------|-------------------------|
| Contact plating | 2 μm Ag |
| Locking element | Stainless steel |
| Shell | Polyamide (PA 6.6) |
| Contacts | Spring Copper (CuSn0.2) |

| Environmental | |
|--------------------------|---|
| Flammability | UL 94 V-0 |
| Protection class | IP65, UL50E enclosure type4 rating in combination with SCNAC-MPX (mated or with closed cap) |
| Temperature range | - 30 °C - +80 °C |