### PPA(-S)(-W) PPB(-S)(-W) PPC(-S)(-W)



# Ceiling/Wall Projector Mount with Adjustable Extension

For Multimedia Projectors up to 50lb (22kg)

PPA and PPB projector mount models are the only projector mounts that offer ceiling and wall mounting options in one out-of-the-box solution while the PPC model delivers a flexible drop length for ceiling mounted projectors. These versatile, ready to install mount models offer the convenience of installation to the ceiling or the wall and provide drop length options without the need of additional accessories. These mount models provide the first true comprehensive projector mounting solution in a single package.

## LB (KG)

Max load: 50lb (22kg)

#### **FEATURES**

- Continuous channel design for uninterrupted drop length or wall extension adjustments
- Three adjustable extension lengths:

PPA models: (ceiling/wall) 12.77"-17.87" (324-454mm) 9.95"-14.06" (253-357mm)

PPB models: (ceiling/wall) 16.77"-25.77" (426-655mm) 13.93"-21.95" (354-558mm)

PPC models: (ceiling only) 23.22"-37.98" (590-965mm)

- Safety catch designed into extension to ensure user and equipment safety
- Mounts to ceiling or wall (according to model) with included wall mount interface
- Spider® Universal Adapter Plate extends up to 17.63" (448mm) to fit most projector models
- Internal cable management within channels for clean, clutter-free appearance
- Includes hardware for installation to a wood joist or concrete
- Specifications:

Tilt: +30°/-5° Roll: ±20° Swivel: ±20°





Safety Catch Mechanism



Wall Adapter Included with PPA & PPB









Model Numbers

WARRANTY: Limited 5-year

PPA(-S)(-W): Ceiling/Wall Projector Mount with Adjustable Extension
PPB(-S)(-W): Ceiling/Wall Projector Mount with Adjustable Extension
PPC(-S)(-W): Ceiling Projector Mount with Adjustable Extension

#### **Product Specifications**


	DIMENSIONS (W x H x D) with adapter plate	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
PPA(-S)(-W)	8.5"-17.63" x 12.77"-17.87" x 8.5"-17.63" (216-448 x 324-454 x 216-448mm)	4.82lb (2.18kg)		Scratch resistant fused epoxy	PPA: Black PPA-S: Silver PPA-W: White PPB: Black PPB-S: Silver PPB-W: White PPC: Black PPC-S: Silver PPC-W: White
PPB(-S)(-W)	8.5"-17.63" x 16.77"-25.77" x 8.5"-17.63" (216-448 x 426-655 x 216-448mm)	5.5lb (2.49kg)	50 lb (22kg)		
PPC(-S)(-W)	8.5"-17.63" x 23.22"-37.98" x 8.5"-17.63" (216-448 x 590-965 x 216-448mm)	6.23lb (2.83kg)			

#### **Package Specifications**


	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE	UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE	
PPA(-S)(-W)	12.06" x 4.25" x 9.31" (306 x 108 x 236mm)	6.59 lb (2.99kg)	PPA: PPA-S: PPA-W:	735029255383 735029255390 735029255406	Wall/ceiling plate, adjustable extension columns, ceiling/		
PPB(-S)(-W)	12.06" x 4.25" x 9.31" (306 x 108 x 236mm)	7.05 lb (3.2kg)	PPB: PPB-S: PPB-W:	735029255413 735029255420 735029255437	wall connection brackets, PPF Projector Mount, Spider Universal Adapter Plate, mounting and projector attachment hardware, assembly instructions	1	
PPC(-S)(-W)	19.37"x 4.37" x 10" (492 x 111 x 254mm)	7.96 lb (3.61kg)	PPC: PPC-S: PPC-W:	735029255444 735029255451 735029255468	Ceiling plate, adjustable extension column, ceiling connection bracket, PPF Projector Mount, Spider <sup>®</sup> Universal Adapter Plate, mounting and projector attachment hardware, assembly instructions		


#### Accessories

ACC-EXC(S)(W): Extension Column




PPA, PPB, PPC HEIGHT						
RANGE X	MINIMUM	MAXIMUM				
PPA	1.23" (31mm)	2.23" (57mm)				
PPB	1.23" (31mm)	2.23" (57mm)				
PPC	1.23" (31mm)	2.23" (57mm)				
RANGE Y	MINIMUM	MAXIMUM				
PPA	11.54" (293mm)	15.64" (397mm)				
PPB	15.54" (395mm)	23.54" (598mm)				
PPC	21.99" (559mm)	35.75" (908mm)				
RANGE Z	MINIMUM	MAXIMUM				
PPA	9.95" (253mm)	14.06" (357mm)				
PPB	13.93" (354mm)	21.95" (558mm)				
PPC	n/a	n/a				






TOP VIEW OF ADAPTER PLATE









20°(± 10°) ROLL FRONT VIEW

35 (-5/+30) TILT SIDE VIEW

#### ARCHITECTS SPECIFICATIONS

20° (  $\pm 10^\circ$  ) SWIVEL TOP VIEW

The Ceiling/Wall Mount shall be Peerless models PPA; PPB; PPC and shall be located where indicated on the plans. It shall feature adjustable +30°/-5° tilt.

It shall be constructed of heavy gauge cold rolled steel and finished with scratch resistant Black, Silver or White Fused Epoxy.

Assembly and installation shall be done according to instructions provided by the manAufacturer.

Peerless Industries, Inc. ■ 2300 White Oak Circle ■ Aurora, IL 60502 ■ (800) 865-2112 ■ (630) 375-5100 ■ Fax: (800) 359-6500 ■ peerless-av.com