

# CMX45/55

Gooseneck Microphone

## AUDAC

### ► Features

- Small, elegant, electret gooseneck microphone
- Supplied with black pop shield
- Great microphone sensitivity
- Windcap included
- Small and slim design
- High quality sound reproduction
- Reduction of feedback to minimum

### ► Applications

Perfect for:

- Conferences
- Churches
- Seminars
- Presentations



The AUDAC CMX45/55 series microphones are small and elegant electret gooseneck microphones.

These are perfect microphones for high-quality reproduction of speech and therefore suitable for conferences, church services and seminars.

The cardioid polar pattern ensures that the microphone is insensitive to feedback loops. The microphone is mounted on a flexible gooseneck, which allows a perfect placement of the microphone.

The CMX45/55 feature a balanced XLR connection and work on any phantom power of 9 to 52 Volt.

These microphones are standard supplied with a black pop shield.

There are two microphones in the CMX serie available with different lengths:

- CMX45 - 45 cm
- CMX55 - 55 cm

### ► Specifications

SYSTEM SPECIFICATIONS		
Frequency response	150 Hz - 20 kHz	
Maximum Current Consumption	500 µA	
Signal to Noise Ratio	58 dB	
Sensitivity Microphone (1V/Pa)	-44 dB	
Maximum Input SPL	120 dB	
Impedance Microphone	2200 Ohm	
PRODUCT FEATURES		
Dimensions	Ø 19 x 453 mm	CMX45
	Ø 19 x 553 mm	CMX55
Weight net	155 g	CMX45
	180 g	CMX55
Construction	Gooseneck 45 cm	CMX45
	Gooseneck 55 cm	CMX55
Connector	3-pin XLR	
Polar Pattern	Cardioid	
Microphone type	Electret	
Colour	Black	
SHIPPING & ORDERING		
Packaging	Carton box	
Shipping weight & Volume	200 g - 0.001 Cbm	
Accessories	Windcap	
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products		