

# PRE26

6 Channel & Two-Zone Stereo Pre-Amplifier

## AUDAC

### ► Features

- Two stereo balanced output zones
- 6 input channels
- Two microphone channels
- 15V Phantom power, Tone control & Talkover
- 1 Balanced stereo line input
- 3 Unbalanced stereo line inputs
- Easy to use
- Excellent sound quality
- Modern and advanced design



### ► Applications

- Restaurants
- Hotels
- Shops
- Warehouses
- Business offices
- Public buildings



The PRE26 is an especially designed preamplifier to meet the demands of the user, without making it too complicated. It contains 2 microphone inputs and 4 stereo line inputs. It is constructed as a dual zone stereo preamplifier and has all the necessary controls and connection possibilities.

On the front of the PRE26, you can find a volume control and a Clip LED indicator for each channel to control the input levels. Each input channel also features 2 buttons and green indication LED's to control the routing of the input signal.

For each output section are a 6 segment LED bar, a master volume control and a 2 band tone control are provided.

At the back of the PRE26, all the necessary connections can be made, featuring 2 XLR microphone inputs in combination with a gain control, a 3 band tone control, a phantom power switch and a talk over switch.

Channel 1 is constructed as a stereo line input channel, fitted with 2 balanced XLR connectors, a stereo/mono switch and a gain control. Channel 2, 3 and 4 are constructed as stereo line input channels, each fitted with 2 RCA connectors and a gain control.

The output section features 2 balanced XLR connectors and a stereo/mono switch for each output zone.

### ► Specifications

SYSTEM SPECIFICATIONS	
Input impedance Mic 1-2	600 Ohm balanced XLR
Input impedance Channel 1	2 x 600 Ohm balanced XLR
Input impedance Channel 2-4	47 kOhm unbalanced cinch / RCA
Input microphone sensitivity	1 mV
Input Channel 1 sensitivity	200 mV
Input Channel 2-4 sensitivity	200 mV
Frequency response -3dB	20 Hz - 20 kHz
THD+N by 1kHz	< 0,1%
Signal to noise ratio	> 90 dB
Output impedance	4 x 600 Ohm balanced XLR
Output level	1.2 V
Power supply	100 - 240 V AC / 50-60 Hz
Phantom power	15V ± 3V
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	482 x 44 x 309 mm
Weight net	3.6 Kg
Mounting	19"
Unit height	1 HE
Construction	Steel
Colour	Black
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight and volume	5 Kg - 0.013 Cbm

\*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products