# Wall Speaker

# **AUDAC**

#### **▶** Features

- Powerful 2 way wall speaker
- True-to-nature sound reproduction
- Available in 3 different colours
- Vertical or horizontal mounting
- Mounting bracket is included
- Easy installation
- Aluminium grill
- Adjustable power tapping

### Applications

- Wide variation of indoor applications
- Private houses
- Halls, Pubs
- Restaurants
- Stores
- Warehouses





The AUDAC WX series speakers are powerful 2-way performance speakers for a wide variety of applications, ensuring true-to-nature, high-fidelity reproduction of music and speech.

They WX302 has a 3" low frequency loudspeaker and a 1" dome tweeter and is built in a synthetic enclosure which makes the speaker suitable for all purposes.

The speaker is suitable for standard home indoor installations to specialized indoor design appliances.

Due to the construction, the speaker can be mounted vertically or horizontally, using the included wall bracket.

This loudspeaker is available in three colours: white, black and silver, and is standard delivered with a wall fixig bracket in the same colour as the speaker.

By means of a recessed adjuster screw at the rear the power can be set in 3 adjustable steps of impedance for 100V and 1 step for 8 Ohm standard low impedance applications.

- 20 Watt, 10 Watt, 5 Watt @ 100 V
- 30 Watt @ 8 Ohm

## **▶** Specifications

| Max. power                          |          | 60 W                      |
|-------------------------------------|----------|---------------------------|
| RMS power                           |          | 30 W                      |
| Line Transformer Power Tap 1        |          | 20 W / 500 Ohm            |
| Line Transformer Power Tap 2        |          | 10 W / 1000 Ohm           |
| Line Transformer Power Tap 3        |          | 5 W / 2000 Ohm            |
| Frequency Response -3dB             |          | 90 Hz - 18 KHz            |
| Frequency Range -10dB               |          | 60 Hz - 20 KHz            |
| Crossover frequency                 |          | 2.5 KHz                   |
| Sensitivity 1W / 1m                 |          | 85 dB                     |
| SPL max W / 1m @ 8 Ohm              |          | 100 dB                    |
| SPL max W / 1m @ 100 Volt           |          | 95 dB                     |
| Impedance                           |          | 8 Ohm                     |
| Crossover                           |          | Passive built-in          |
| Horizontal coverage                 |          | 100°                      |
| Vertical coverage                   |          | 100°                      |
| PRODUCT FE                          | EATURES  |                           |
| Dimensions (Width x Height x Depth) |          | n) 199 x 129 x 120 mm     |
| Weight net                          |          | 1.66 Kg                   |
| Drivers                             | HF       | 1"                        |
|                                     | LF       | 3"                        |
| Construction                        |          | ABS housing               |
| Mounting                            |          | Mounting bracket          |
| Front finish                        |          | Aluminium grill           |
| Connectors                          |          | Cable clamps              |
| Colour                              |          | White (RAL 9010) WX302/W  |
|                                     |          | Black (RAL 9005) WX302/B  |
| OLUBBINO & ODDEDINO                 |          | Silver (RAL 9006) WX302/S |
| SHIPPING &                          | ORDERING |                           |
| Packaging                           |          | Carton box                |
| Shipping weight & volume            |          | 3.9 Kg - 0.016 Cbm        |
| Accessory included                  |          | Mounting bracket          |

\*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products